Timeless Classics Collection Specifications



Timeless Classics Collection Specifications

	Construction: Engineered High Density Ply Core Hardwood with Tongue and Groove		Edge Profile: 3-4mm Micro Beveled Edges and Ends
	Species: Hickory and Maple		Installation: Nail, Staple, Glue, Float; Above Grade, At Grade, Below Grade
	Dimensions: 1/2" X 4"/5"/6" (Random widths) or 6" (Fixed width) X 15"-60" (Random Lengths)		Surface Treatment: Hand Scraped
2mm	Thickness of Surface Layer: 2mm	GLOSS	Gloss: Hickory: 6-10 degree; Maple: 20-24 degree
	Cutting Method: Rotary		Moisture Content: 6%-9%
ABC	Grade: ABCD		Color Variation: Water-based Coloring

Finish:

UV/6 primer2 finish, Sherwin-Williams+overmat

Assembling Gap: ≤0.20mm Length Deviation: ±0.5mm Width Deviation: ±0.15mm Thickness Deviation: ±0.2mm Reactive Stain: No Surface Abrasion Resistance: ≥300r, S-33 Sand paper Film Hardness: ≥2H Static Bending Strength: No Moisture Content: 6%-9%



Area per carton: 4"/5"/6": 34.45 Sqft. per Carton; 6": 20.67 Sqft. per Carton **Weight per carton:** 4"/5"/6": 60 Lbs; 6": 37 Lbs

Warranties: 50 year residential finish warranty. 5 year commercial warranty. Please visit www.californiaclassicsfloors.com for the most current warranty information.



Environmental

Certifications: Floor Score Certified Carb II Compliant: Yes Lacy Act Compliant: Yes